

Trade name: M-Plast Reinigungs-Benzin 5203

Substance number: 336840

Version: 4 / CH

Date revised: 17.12.2018

Replaces Version: 3 / CH

Print date: 04.10.19

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

M-Plast Reinigungs-Benzin 5203

Item No. 33684001

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Industrial solvent

1.3. Details of the supplier of the safety data sheet

Address/Manufacturer

Hänseler AG

Industriestrasse 35

9100 Herisau

Telephone no. 0041 (0)71 353 58 58

E-mail address of sdb@haenseler.ch

person responsible

for this SDS

1.4. Emergency telephone number

Switzerland :145 / Abroad +41 (0)44 251 51 51

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 2 H225

Skin Irrit. 2 H315

STOT SE 3 H336

Asp. Tox. 1 H304

Aquatic Chronic 2 H411

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008

For explanation of abbreviations see section 16.

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Danger

Hazard statements

H225

Highly flammable liquid and vapour.

H315

Causes skin irritation.

H336

May cause drowsiness or dizziness.

H304

May be fatal if swallowed and enters airways.

Trade name: M-Plast Reinigungs-Benzin 5203

Substance number: 336840

Version: 4 / CH

Date revised: 17.12.2018

Replaces Version: 3 / CH

Print date: 04.10.19

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P331 Do NOT induce vomiting.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane;
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics; Hydrocarbons, C6,
isoalkanes, <5% n-hexane

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

M-Plast Reinigungs-Benzin 5203

Hazardous ingredients**Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

EINECS no. 921-024-6

Registration no. 01-2119475514-35-XXXX

Concentration \geq 50 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 2	H225
Skin Irrit. 2	H315
STOT SE 3	H336
Asp. Tox. 1	H304
Aquatic Chronic 2	H411

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

EINECS no. 927-510-4

Registration no. 01-2119475514-35-XXXX

Concentration \geq 50 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 2	H225
Skin Irrit. 2	H315
STOT SE 3	H336
Asp. Tox. 1	H304
Aquatic Chronic 2	H411

Hydrocarbons, C6, isoalkanes, <5% n-hexane

CAS No. 64742-49-0

EINECS no. 931-254-9

Registration no. 01-2119484651-34-XXXX

Concentration \geq 25 < 50 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 2	H225
Skin Irrit. 2	H315
STOT SE 3	H336
Asp. Tox. 1	H304

Trade name: M-Plast Reinigungs-Benzin 5203

Substance number: 336840

Version: 4 / CH

Date revised: 17.12.2018

Replaces Version: 3 / CH

Print date: 04.10.19

Aquatic Chronic 2 H411

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated, soaked clothing immediately and dispose of safely. Remove affected person from danger area.

After inhalation

Remove the casualty into fresh air and keep him calm. Seek medical advice immediately. If the patient is likely to become unconscious, place and transport in stable sideways position.

After skin contact

Wash off immediately with soap and water and rinse well. Consult a doctor if skin irritation persists.

After eye contact

Separate eyelids, wash the eyes thoroughly with water (15 min.).

After ingestion

Do not induce vomiting. Summon a doctor immediately. Rinse out mouth and give plenty of water to drink. Administer activated charcoal.

4.2. Most important symptoms and effects, both acute and delayed

Dizziness, Unconsciousness, Nausea, Vomiting, CNS Disturbance, Narcosis, respiratory moderation

4.3. Indication of any immediate medical attention and special treatment needed

Hints for the physician / hazards

In the case of swallowing with subsequent vomiting, aspiration of the lungs can occur which can lead to chemical pneumonia or asphyxiation.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide, Foam, Dry powder

Non suitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Carbon monoxide (CO); Forms explosive mixture with air are possible.

5.3. Advice for firefighters

Special protective equipment for fire-fighting

Wear full protective suit. Use self-contained breathing apparatus.

Other information

Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep away unprotected persons.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not empty into drains, caverns and

Trade name: M-Plast Reinigungs-Benzin 5203

Substance number: 336840

Version: 4 / CH

Date revised: 17.12.2018

Replaces Version: 3 / CH

Print date: 04.10.19

basements. Advise water authority if spillage has entered water course or drainage system.

6.3. Methods and material for containment and cleaning up

Pick up with absorbent material (eg sand, kieselgur, acid binder, universal binder, sawdust). When picked up, treat material as prescribed under Section 13 "Disposal". Ensure adequate ventilation.

6.4. Reference to other sections

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Provide good room ventilation even at ground level (vapours are heavier than air). Handle and open container with care. Avoid formation of aerosols. Take action to prevent static discharges.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Vapours can form an explosive mixture with air. Use explosion-proof equipment/fittings and non-sparking tools. Risk of explosion if the liquid enters the drains.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

explosion proof. Provide solvent-resistant and impermeable floor.

Further information on storage conditions

Keep container tightly closed, cool and dry. Keep container tightly closed. Protect from direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Derived No/Minimal Effect Levels (DNEL/DMEL)

Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	773	mg/kg
Source	Safety Data Sheet Supplier	

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	2035	mg/m ³
Source	Safety Data Sheet Supplier	

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	

Trade name: M-Plast Reinigungs-Benzin 5203

Substance number: 336840

Version: 4 / CH

Date revised: 17.12.2018

Replaces Version: 3 / CH

Print date: 04.10.19

Concentration	699	mg/kg
Source	Safety Data Sheet Supplier	

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	

Concentration	608	mg/m ³
Source	Safety Data Sheet Supplier	

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	

Concentration	699	mg/kg
Source	Safety Data Sheet Supplier	

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	

Concentration	300	mg/kg/d
Source	Safety Data Sheet Supplier	

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	

Concentration	2085	mg/m ³
Source	Safety Data Sheet Supplier	

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	

Concentration	149	mg/kg/d
Source	Safety Data Sheet Supplier	

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	

Concentration	477	mg/m ³
Source	Safety Data Sheet Supplier	

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	

Trade name: M-Plast Reinigungs-Benzin 5203

Substance number: 336840

Version: 4 / CH

Date revised: 17.12.2018

Replaces Version: 3 / CH

Print date: 04.10.19

Concentration	149	mg/kg/d
---------------	-----	---------

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	13964	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	5306	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	1377	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	1137	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	1301	mg/kg/d

8.2. Exposure controls**Exposure controls**

See Section 7. No measures exceeding the ones mentioned necessary.

General protective and hygiene measures

Keep away from food-stuffs, beverages and feed-stocks. Wash hands before breaks and after work. Store work clothing separately. At work do not eat, drink, smoke or take drugs. Do not inhale gases/vapours/aerosols. Avoid contact with skin and eyes.

Respiratory protection

Breathing apparatus in the event of aerosol or mist formation. Gas filter class A1.

Hand protection

Gloves (solvent-resistant)	
Appropriate Material	nitrile rubber - NBR
Material thickness	0.35 mm
Not suitable: rubber gloves	
Not suitable: PVC gloves	
Not suitable: leather gloves	

Trade name: M-Plast Reinigungs-Benzin 5203

Substance number: 336840

Version: 4 / CH

Date revised: 17.12.2018

Replaces Version: 3 / CH

Print date: 04.10.19

Not suitable: gloves made of thick material

Eye protection

Tightly fitting safety glasses

Body protection

Solvent-resistant protective clothing

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Form	liquid		
Colour	colourless		
Odour	slightly perceptible		
Odour threshold			
Remarks	No data available		
pH value			
Remarks	No data available		
Freezing point			
Remarks	No data available		
Initial boiling point and boiling range			
Value	48	to	105 °C
Flash point			
Value	< 0		°C
Method	DIN 51755		
Evaporation rate			
Remarks	No data available		
Upper/lower flammability or explosive limits			
Lower explosion limit	0.6		%(V)
Upper explosion limit	7.4		%(V)
Vapour pressure			
Value	190		hPa
Temperature	20	°C	
Vapour density			
Remarks	No data available		
Density			
Value	0.688		g/cm ³
Temperature	20	°C	
Method	ASTM D 1298		
Solubility in water			
Remarks	virtually insoluble		
Partition coefficient: n-octanol/water			
M-Plast Reinigungs-Benzin 5203			
log Pow	> 3		
Auto-ignition temperature			
Value	> 200		°C
Efflux time			
Remarks	No data available		

9.2. Other information

Trade name: M-Plast Reinigungs-Benzin 5203

Substance number: 336840

Version: 4 / CH

Date revised: 17.12.2018

Replaces Version: 3 / CH

Print date: 04.10.19

Other information

Forms explosive mixture with air are possible.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reactions when stored and handled according to prescribed instructions.

10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3. Possibility of hazardous reactions

No decomposition if stored and applied as directed.

10.4. Conditions to avoid

Heat. Flames. Sparks

10.5. Incompatible materials

Explosive, Formation of explosive gas/air mixtures.

10.6. Hazardous decomposition products

Flammable gases/vapours

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute oral toxicity (Components)****Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

Species	rat	
LD50	> 5000	mg/kg
Method	OECD 401	

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Species	rat	
LD50	> 5840	mg/kg
Method	OECD 401	
Source	Analogous	

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Species	rat	
LD50	> 5000	mg/kg
Method	OECD 401	

Acute dermal toxicity (Components)**Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

Species	rat	
LD50	> 2000	mg/kg
Method	OECD 402	

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Species	rat	
LD50	> 2920	mg/kg
Method	OECD 402	
Source	Analogous	

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Species	rat	
LC50	> 3000	mg/kg
Method	OECD 402	

Trade name: M-Plast Reinigungs-Benzin 5203

Substance number: 336840

Version: 4 / CH

Date revised: 17.12.2018

Replaces Version: 3 / CH

Print date: 04.10.19

Acute inhalative toxicity (Components)**Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

Species	rat		
LC50	>	20	mg/l
Duration of exposure	4	h	
Administration/Form	Vapors		
Method	OECD 403		

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Species	rat		
LC50	>	23.3	mg/l
Duration of exposure	4	h	
Administration/Form	Vapors		
Method	OECD 403		
Source	Analogous		

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Species	rat		
LC50	>	20	mg/l
Duration of exposure	4	h	
Administration/Form	Vapors		
Method	OECD 403		

Skin corrosion/irritation**M-Plast Reinigungs-Benzin 5203**

Remarks	Irritates the mucous membrane.
---------	--------------------------------

M-Plast Reinigungs-Benzin 5203

Remarks	Repeated and prolonged skin contact may lead to defatting and irritation of the skin.
---------	---

Serious eye damage/irritation**M-Plast Reinigungs-Benzin 5203**

Remarks	slightly irritating (Eye)
---------	---------------------------

Sensitization**M-Plast Reinigungs-Benzin 5203**

Remarks	No sensitisation effect known.
---------	--------------------------------

Sensitization (Components)**Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

evaluation	non-sensitizing
------------	-----------------

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

evaluation	non-sensitizing
------------	-----------------

Hydrocarbons, C6, isoalkanes, <5% n-hexane

evaluation	non-sensitizing
------------	-----------------

Subacute, subchronic, chronic toxicity**M-Plast Reinigungs-Benzin 5203**

Remarks	Chronic exposure causes damage of respiratory organs.
---------	---

M-Plast Reinigungs-Benzin 5203

Remarks	Chronic exposure may cause serious damage of skin.
---------	--

Mutagenicity (Components)**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics**

evaluation	No experimental indications on genotoxicity in vivo found.
Source	Analogous

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Trade name: M-Plast Reinigungs-Benzin 5203

Substance number: 336840

Version: 4 / CH

Date revised: 17.12.2018

Replaces Version: 3 / CH

Print date: 04.10.19

evaluation No experimental indications on genotoxicity in vivo found.
Source Analogous

Experience in practice

Causes a numb feeling.

Other information

Quantitative data concerning toxicity are not available.

SECTION 12: Ecological information**12.1. Toxicity****Fish toxicity****M-Plast Reinigungs-Benzin 5203**

LC50	<	10	mg/l
------	---	----	------

Fish toxicity (Components)**Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

Species	rainbow trout (Oncorhynchus mykiss)		
LC50	11.4		mg/l
Duration of exposure	96	h	

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Species	rainbow trout (Oncorhynchus mykiss)		
LC50	13.4		mg/l
Duration of exposure	96	h	

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Species	red killifish		
LC50	1		mg/l
Duration of exposure	48	h	
Source	Analogous		

Daphnia toxicity (Components)**Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

Species	Daphnia magna		
NOEC	0.17		mg/l
Duration of exposure	21	d	

Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Species	Daphnia magna		
LOEC	0.32		
Duration of exposure	21	d	

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Species	Daphnia magna		
NOEC	0.17		mg/l
Duration of exposure	21	d	
Source	Analogous		

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Species	Daphnia magna		
LC50	3.87		mg/l
Duration of exposure	48	h	
Source	Analogous		

Algae toxicity**M-Plast Reinigungs-Benzin 5203**

IC50	<	100	mg/l
------	---	-----	------

Algae toxicity (Components)

Trade name: M-Plast Reinigungs-Benzin 5203

Substance number: 336840

Version: 4 / CH

Date revised: 17.12.2018

Replaces Version: 3 / CH

Print date: 04.10.19

Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Species	Pseudokirchneriella subcapitata		
EC50	30		mg/l
Duration of exposure	72	h	
Method	OECD 201		

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Species	Pseudokirchneriella subcapitata		
NOEC	10		mg/l
Duration of exposure	72	h	
Source	Analogous		

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Species	Pseudokirchneriella subcapitata		
EC50	10	to 30	mg/l
Duration of exposure	72	h	
Source	Analogous		

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Species	Pseudokirchneriella subcapitata		
ErC50	55		mg/l
Duration of exposure	72	h	
Source	Analogous		

Hydrocarbons, C6, isoalkanes, <5% n-hexane

NOEC	30		mg/l
Duration of exposure	72	h	

Bacteria toxicity**M-Plast Reinigungs-Benzin 5203**

EC50	10		mg/l
------	----	--	------

12.2. Persistence and degradability**General information**

For this subsection there is no ecotoxicological data available on the product as such.

Biodegradability (Components)**Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

Value	81		%
Duration of test evaluation	28	d	
Source	Readily biodegradable		
	Analogous		

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Value	98		%
Duration of test evaluation	28	d	
Source	Readily biodegradable		
	Analogous		

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Value	98		%
Duration of test evaluation	28	d	
Source	Readily biodegradable		
	Analogous		

12.3. Bioaccumulative potential**Partition coefficient: n-octanol/water****M-Plast Reinigungs-Benzin 5203**

log Pow	>	3	
---------	---	---	--

12.4. Mobility in soil

Trade name: M-Plast Reinigungs-Benzin 5203

Substance number: 336840

Version: 4 / CH

Date revised: 17.12.2018

Replaces Version: 3 / CH

Print date: 04.10.19

General information

For this subsection there is no ecotoxicological data available on the product as such.

12.5. Results of PBT and vPvB assessment

General information

For this subsection there is no ecotoxicological data available on the product as such.

Evaluation of persistence and bioaccumulation potential (Components)

Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

The Substance doesn't meet PBT/vPvB-criteria

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

The Substance doesn't meet PBT/vPvB-criteria

Hydrocarbons, C6, isoalkanes, <5% n-hexane

The Substance doesn't meet PBT/vPvB-criteria

12.6. Other adverse effects

General information / ecology

Toxic for aquatic organisms. Do not allow it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

Disposal in compliance with local and national regulations.

Disposal recommendations for packaging

Dispose of as unused product.

SECTION 14: Transport information

Trade name: M-Plast Reinigungs-Benzin 5203




Substance number: 336840

Version: 4 / CH

Date revised: 17.12.2018

Replaces Version: 3 / CH

Print date: 04.10.19

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
Tunnel restriction code	D/E		
14.1. UN number	3295	3295	3295
14.2. UN proper shipping name	HYDROCARBONS, LIQUID, N.O.S. (Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)	HYDROCARBONS, LIQUID, N.O.S. (Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)	HYDROCARBONS, LIQUID, N.O.S. (Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)
14.3. Transport hazard class(es)	3	3	3
Label			
14.4. Packing group	II	II	II
Special provision	640D		
Limited Quantity	1 I		
Transport category	2		

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Water Hazard Class (Germany)

Water Hazard Class (Germany) WGK 3

Remarks Classification according to Annex 4 VwVwS

National regulations Switzerland

Swiss Toxicity Class 4
SFOPH T no. G-4860

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Hazard statements listed in Chapter 3

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

CLP categories listed in Chapter 3

Aquatic Chronic 2 Hazardous to the aquatic environment, chronic, Category 2

Trade name: M-Plast Reinigungs-Benzin 5203

Substance number: 336840

Version: 4 / CH

Date revised: 17.12.2018

Replaces Version: 3 / CH

Print date: 04.10.19

Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 2	Flammable liquid, Category 2
Skin Irrit. 2	Skin irritation, Category 2
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: ***
This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.